

BC LIGHT, BLUEBERRY & BOUNDARY LAKE GATHERING PETROLEUM SPECIFICATIONS Effective : Aug 10, 2015	Units	Test Method	BOUNDARY LAKE	BC LIGHT
Absolute Density at 15°C	kg/m3	ASTM D5002	904-799	876-799
Vapour Pressure (VPCR₄@37.8C)	kPaa	ASTM D6377	◀95	◀95
Receipt Temperature	°C °C		40 (max.) 0.0 (min.)	40 (max.) 0.0 (min.)
Moisture and Contaminant Content ^{(1) (2)}	vol%	ASTM D4007	◀ 0.5	◀ 0.5
Colour		ASTM D1500	◀ 8.0	◀8.0
PH of contained water ⁽²⁾			▶ 5.0 & ◀7.0	▶ 5.0 & ◀7.0
Total Sulphur	wt%	ASTM D4294	▶ 0.5 & ◀ 1.2	◀ 0.5
Organic Chlorides in Whole Crude	wppm	ASTM D4929	◀ 1	◀ 1
Hydrogen Sulphide in the Liquid Phase	wppm	ASTM D5623	◀ 100 ⁽³⁾	◀ 100 ⁽³⁾
Olefins, Total	wt%	H NMR	◀ 1	◀ 1
Phosphorous in Volatile fraction	wppm	ICP AES D86 (250°C cut)	◀1.5	◀1.5
Total Salt	g/m3		◀ 285	◀ 285
Viscosity @ 10.0 °C	cSt	ASTM D445	◀35	
NOTES: 1. Contaminant content means all non-hydrocarbon materials excluding Nitrogen and Carbon Dioxide. 2. No free water at -29°C. 3. Guideline only. The symbol "◀" designates less than and "▶" designates				